

ULTRAGREASE TF SPRAY

HIGH PERFORMANCE GREASE SPRAY

DESCRIPTION

Synthetic base and PTFE grease spray. An inorganic thickener with high temperature resistance is used. It contains PTFE. It is a lubricant approved for incidental food contact, classified as H1 by NSF.

APPLICATIONS

- Lubrication in severe working conditions: exposition to moisture, vibration, steam, dirtiness, high loads and pressures.
- Bottling plants, food packaging (closing machines in food canning industry, fruit and vegetable stores), textile finishing, water waste treatment plants, harbour equipment, ships, in mechanisms like:
 - Chains, slide ways and eccentrics.
 - Spindles and valves.
 - Small bearings

PROPERTIES

- Excellent adherence, even in presence of cold or hot water, salt water and steam.
- It protects from corrosion.
- From -20 up to +160°C. Peak temperatures up to +200°C.
- High resistance to aging and shearing.
- Increased load carrying capacity and EP properties.

HOW TO USE:

Stir energetically before use. Keep the bottle vertically, as much during the storage as when using it.

QUALITY LEVEL

Certified NSF H1, nº Register 149168
 Certified HALAL, nº IH-682/2.4/B/76/4/4



TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	-	Translucent white grease	-
Dropping point	ASTM D-566	n.m.	°C
Base oil Viscosity 40 °C	ASTM D 445	1000	cSt
Weld load, 4 ball test	ASTM D-2596	200	kg
Wear scar, 4 ball test	ASTM D-2266	0,42	mm
Oil separation (100 °C)	ASTM D-6184	0,2	%

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

ULTRAGREASE TF SPRAY

HIGH PERFORMANCE GREASE SPRAY

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 60 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

REV: 09/23

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

COMPAÑIA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com
www.cogelsa.com

